



The Many Beautiful Faces of Metal.



Offering the classic looks of slate, tile and wood for commercial and residential roofs.

MetalWorks Steel Shingles

MetalWorks® Steel Shingles pair the latest looks with trusted G-90 steel. And whether it's the sleek look of tile, the dramatic look of wood or the classic look of slate, MetalWorks products provide the right shingle for any taste. The shingles are available in a full array of colors, all of which are ENERGY STAR® qualified.

A beautiful choice for a wide range of residential and commercial applications.

Features & Benefits

G-90 Steel Construction

Recognized as the industry standard

KYNAR 500®/HYLAR 5000® Finish

A hardy, resin-based coating

Can Be Used for Reroofing Applications

Install over up to two layers of asphalt shingles*

Environmentally Conscious

100% recyclable

50-year Limited Warranty†

Shingles begin to age as soon as they are exposed to nature, and buildings experience aging factors differently. Because it's difficult to predict how long shingles will last, TAMKO offers a 50-year Limited Warranty on MetalWorks shingles.

- 25-year Full Start Period ▪
- 30-year Finish Limited Warranty ▪
- 50-year Limited Warranty Coverage for Winds up to 110 mph ▪

Four-way Locking System

Utilized for effective installation

Energy Star® Qualified

*Check your local building code.

† To obtain a copy of TAMKO's Limited Warranty, visit us online at tamko.com or call us at 1-800-641-4691.

StoneCrest® Slate Steel Shingles

Create a dramatic look that closely replicates the random finish of natural slate. The double-stamped manufacturing process creates stunning beauty.

StoneCrest Slate
Vermont Blue



StoneCrest® Tile Steel Shingles

Create the distinctive look of smooth, uniform tile. For those who appreciate a contemporary and refined appearance.

StoneCrest Tile
Quaker Green



AstonWood® Steel Shingles

Combine the warmth and appeal of cedar shingles with galvanized steel to produce a roofing product that emulates the rich, deep, hand-hewn texture of wood.

AstonWood
Timber Brown



Colors

SS = StoneCrest Slate

AW = AstonWood

ST = StoneCrest Tile

Custom Colors

For a color requirement that does not appear in Standard Colors, please contact TAMKO to inquire about our Special Color Program.

SEQUOIA RED • SS • AW •	VERMONT BLUE • SS • AW • ST •	TIMBER BROWN • AW •
FOREST GREEN • AW •	SIERRA SLATE GREY • SS • AW • ST •	RIVER ROCK BROWN • SS • AW •
BRITE RED • AW •	QUAKER GREEN • SS • ST •	CANYON COPPER BRONZE • AW •

NOTE: REPRODUCTION OF THESE COLORS IS AS ACCURATE AS OUR PRINTING WILL PERMIT. TAMKO® RECOMMENDS VIEWING AN ACTUAL ROOF INSTALLATION PRIOR TO FINAL COLOR SELECTION FOR THE FULL IMPACT OF COLOR BLENDING AND PATTERNS.



TW Metal & Tile Underlayment

Used for application under metal roofs, this 75 mil self-adhering underlayment features a fiberglass mat, rubberized asphalt, polymer film surfacing and a split treated release film. The underlayment is UL Classified as a Prepared Roofing Accessory and ICC-ES ESR-1252.

StoneCrest Slate
River Rock Brown



Striking Modern Appeal.
And ENERGY STAR® qualified.



StoneCrest Slate
Sierra Slate Grey



StoneCrest Slate
Sequoia Red



StoneCrest Slate
Vermont Blue



StoneCrest Slate
Quaker Green

METALWORKS® Steel shingles combine the classic and contemporary looks of slate, tile and wood with ENERGY STAR qualification.

All MetalWorks shingles are ENERGY STAR qualified and listed by the Cool Roof Rating Council (CRRC).




ENERGY STAR is a joint program of the U.S. Environmental Protection Agency and the U.S. Department of Energy. Consult your product manufacturer, roofing contractor or call 1-888-STAR-YES (1-888-782-7937) for more information. ENERGY STAR is only available in the United States.




The Cool Roof Rating Council (CRRC) is an independent nonprofit organization that lists a third-party rating system for the radiative properties of roof surfacing materials.

MetalWorks® Steel Shingles


AstonWood® Steel Shingle
30 pc. per carton/98.4 sq. ft. per carton




StoneCrest® Slate and StoneCrest® Tile Steel Shingles
15 pc. per carton/49.2 sq. ft. per carton




Metal Accessories




Starter/Eave Flashing
10 pc. per carton/10' length




Gable/Rake Flashing
10 pc. per carton/10' length




Valley
5 pc. per carton/10' length




Sidewall Flashing
5 pc. per carton/10' length



J-Channel
10 pc. per carton/
10' length



Hip Cap Tapered
StoneCrest or AstonWood
50 pc. per carton/1' length




12" Ridge Cap
25 pc. per carton/
1' length



Trim Coil
22-1/4" x 50'



Clip
400 per carton/
100+/- per square




Snow Guard
100 pc. per carton



Colored Screws
0.5-lb. bag of 50 pc.

Non-Metal Accessories



Hip & Ridge Seal
4" x 50'



Touch-up Paint
2-oz. bottle

STONECREST SLATE

- Painted galvanized steel
- Minimum slope: 3" in 12"
- Shingle width—overall: 39-3/4"
- Shingle height—overall: 12-5/8"
- Shingle exposure: 12"
- Shingles per box: 15 panels
- Coverage per box: 49.2 sq. ft. (approx. 1/2 square)
- Shingle material: 28 gauge nominal 0.0162" (0.066802 cm) thickness, including G-90 galvanization and paint coatings. Exterior finish is fluoropolymer (PVDF) with anticorrosive primer, 1 mil dry film thickness. Interior finish is a wash coat with anticorrosive primer, 0.6 mil dry film thickness.
- Clip: 1-1/4" wide x 2-1/8" long x 0.20" deep
- Clip material: 0.015" thick, G-90 galvanized steel

ASTONWOOD

- Painted galvanized steel
- Minimum slope: 3" in 12"
- Shingle width—overall: 39-3/4"
- Shingle height—overall: 12-5/8"
- Shingle exposure: 12"
- Shingles per box: 30 panels
- Coverage per box: 98.4 sq. ft. (approx. 1 square)
- Shingle material: 30 gauge nominal 0.0135" (0.03429 cm) thickness, including G-90 galvanization and paint coatings. Exterior finish is fluoropolymer (PVDF) with anticorrosive primer, 1 mil dry film thickness. Interior finish is a wash coat with anticorrosive primer, 0.6 mil dry film thickness.
- Clip: 1-1/4" wide x 2-1/8" long x 0.20" deep
- Clip material: 0.015" thick, G-90 galvanized steel

STONECREST TILE

- Painted galvanized steel
- Minimum slope: 3" in 12"
- Shingle width—overall: 39-3/4"
- Shingle height—overall: 12-5/8"
- Shingle exposure: 12"
- Shingles per box: 15 panels
- Coverage per box: 49.2 sq. ft. (approx. 1/2 square)
- Shingle material: 28 gauge nominal 0.0162" (0.066802 cm) thickness, including G-90 galvanization and paint coatings. Exterior finish is fluoropolymer (PVDF) with anticorrosive primer, 1 mil dry film thickness. Interior finish is a wash coat with anticorrosive primer, 0.6 mil dry film thickness.
- Clip: 1-1/4" wide x 2-1/8" long x 0.20" deep
- Clip material: 0.015" thick, G-90 galvanized steel

Building Products for the Professional

Information included in this brochure was current at the time of printing. To obtain a copy of the most current version of this brochure or TAMKO's Limited Warranty, visit us online at tamko.com or call us at 1-800-641-4691.

Roofs featured on cover from left to right are AstonWood Timber Brown, StoneCrest Slate Sierra Slate Grey and StoneCrest Tile Vermont Blue.

©2015 TAMKO Building Products, Inc.
TAMKO, MetalWorks, StoneCrest and AstonWood are registered trademarks of TAMKO Building Products, Inc.
Kynar 500 is a registered trademark of Arkema, Inc.
Hylar 5000 is a registered trademark of Solvay Solexis, Inc.
ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency.

71949 0815

TAMKO
BUILDING PRODUCTS

P.O. Box 1404 • Joplin, MO 64802-1404
1-800-641-4691
tamko.com

